

## Cirrus 80



Cirrus 80			
Nominal Power output	at 10°C	300/600 W	450/800 W
Recommended fuse	at 115 V / 230 V	5	6
Time delay	Amps		
Fan volumetric flow, approximate	(m <sup>3</sup> /hr)	35	35
Fan lifetime	at 40°C L10, hours	43.500	43.500
Fan operating temperature	°C	- 40 to +50	- 40 to +50
Nominal Input voltage		115 V / 230 VAC	115 V / 230 VAC
Dimensions (mm)	cross section	82 x 110	82 x 110
	length	150	150
Ingress Protection		IP 20	IP 20
Weight	(kg)	0.785	0.785
Finger guards	inlet and outlet	Y	Y

### Ordering Example:

Type	Power	Heater Voltage	DIN clip	Filter
			1 / 0	1 / 0
C 80	600 W	230 V	1	1

Order Code Example: C80 – 600 W – 230 V – 1 – 1

- |  |  |
|--|--|
| <b>Features:</b> <ul style="list-style-type: none"> <li>- High power to size ratio</li> <li>- Lightweight</li> <li>- Easy to fit</li> <li>- Screw terminals for easy wiring</li> <li>- Dual power feature</li> <li>- Independent fan circuit to aid climate cooling</li> </ul> | <b>Options:</b> <ul style="list-style-type: none"> <li>- Filter Assembly*</li> <li>- Fixings - 35mm DIN Rail clip (EN50022)</li> </ul> |
|--|--|



\* Typical power reduction of 10% when 30 PPI filter fixed. Data is given for illustration purposes only and does not release the customer from independent application tests.

DBK David+Baader GmbH

Components

Rheinstrasse 72 - 74  
D - 76870 Kandel

Phone: + 49 (0) 72 75 7 03 - 231  
Fax: + 49 (0) 72 75 7 03 - 249

info@dbk-group.de  
www.dbk-components.com